

SEMI-COMMERCIAL & RESIDENTIAL CARTRIDGE FILTERS



SYSTEM 3® MOD MEDIA
Filters-SM Series
by Sta-Rite

Simply Smarter.

One cleaning for an entire season?

Sta-Rite's System3® Mod Media™ filters handle 2-3 times more dirt than other filters to deliver maintenance-free performance for up to a full season. Featuring perfectly balanced flow and integral manifold design, these filters are engineered to deliver the ultimate in labor-savings. System3® Mod Media™ filters are ideal for inground pools, inground hot tubs and water features.

Performing to a higher standard

Based on Sta-Rite's extensive research in filtration and media science, System3 Mod Media filters make Ultra-Capacity Filtration™ a reality. Unlike conventional "cartridges," these filters combine a patented balanced flow and integral manifold design, plus an easily-cleaned media element. Modular filter tanks permit quick change of filter media. The result is a filter system that not only requires less frequent cleaning, but is also easy to clean.



The System3 Mod Filter is constructed of Dura-Glas® high-density composite resin to weather the elements for long, dependable life. And its sleek, contemporary appearance and matte black finish looks attractive in any pool setting.

Filter Sizing						
Cat. No.	Sq. Ft. of Area	Maximum Flow	Pool Size 8 Hr. Rate*	Pool Size 6 Hr. Rate*	Port Size	Price
S7M120	300	100 gpm	36,000-48,000	27,000-36,000	2	\$1,072.00
S8M150	450	125 gpm	45,120-60,000	33,840-45,000	2	\$1,406.00

- Patented balanced-flow tank hydraulics direct water through each side of the filter module for uniform dirt loading, no clogging and long, unattended operation.
- Complete media coverage combined with shallow pleats for greater dirt holding capacities, longer filter cycles and less cleaning.
- Shallow pleat design also permits quick and thorough cleaning- just rinse the module with a hose.

CLEAN & CLEAR® PLUS FILTERS

Fiberglass Reinforced Polypropylene Tank

Clean & Clear® Plus Filters have a corrosion resistant injection molded filter tank featuring superior strength and reliability. The cartridge assembly uses four easy to clean, non-woven, polyester cartridges. Each filter is supplied with a bulkhead union set for easy installation.



Featured Highlights:

- NSF listed
- Superior strength
- Large filter area for increased dirt capacity
- 1-1/2 in., 100% drain clean-out port
- Continuous High Flow™ internal air relief
- Base and plumbing kits now available
- Injection molded tank
- Balanced hydraulic flow
- Tension Control™ clamp
- 100% factory tested
- Black bulkhead unions
- High Flow manual air relief valve

Cat. No.	Model No.	Sq. Ft.	Tank Height	Price
16-0310	CCP240	240	37"	\$793.00
16-0340	CCP320	320	43"	\$949.00
16-0301	CCP420	420	49"	\$1,077.00
16-0332	CCP520	520	56"	\$1,333.00

POSI-CLEAR POOL/SPA CARTRIDGE FILTER

PXC Series—Rugged ABS thermoplastic pool/spa cartridge filter for swimming pools and spas, both residential and commercial. ABS non-corrosive tank with a 10 year warranty. Posi-lok ring provides quick, safe access to internals for servicing. Fast venting by extra large directional air vent. Available in 4 sizes, all models include 2" inlet and outlet ports.

Catalog No.	Filter Area (sq. ft.)	Optimal* Performance at this GPM	Flow Rated** GPM/sq. ft.	Turnover Rate (Gallons) (Flow Rate x 60 x Hours)			Tank Port Size	Approx. Ship Weight (lbs.)	Price
				6 hours	8 hours	10 hours			
PXC75	75	38 - 56	28 - 75	10-27,000	13-36,000	16-45,000	2"	22	\$332.00
PXC95	95	48 - 71	36 - 95	12-34,000	17-45,000	21-57,000	2"	23	\$386.00
PXC125	125	63 - 94	47 - 125	16-45,000	22-60,000	28-75,000	2"	29	\$468.00
PXC150	150	75 - 112	56 - 150	20-54,000	26-72,000	33-90,000	2"	30	\$544.00



* Operating at this GPM will provide the longest filter cycles combined with the best and greatest dirt loading capacity.
** Based on NSF recommended flow rate for commercial at .375 GPM per square foot.
NOTE: Operating Limits — designed for maximum continual operating pressure of 50 PSI. Maximum water temperature (internal filter) 104°F (40°C).

STA-RITE POSI-FLO PMT SERIES CARTRIDGE FILTERS

Features:

- Quality glass-reinforced thermo plastic construction throughout for corrosion and weather resistance.
- Top opening clamp and knob assembly is proven safe & sure
- Additional bottom clamp assembly for extra ease of service
- Thermoplastic body and lid assemblies retro-fit to all original Posi-Flo bases
- Available in 50, 70, 100 & 135 sq. ft.

Cat No.	Model No.	Sq. Ft. of Filter Area	Max. Flow Rate 6 P.M. Residential	Commercial	Price	Shipping Weight
PTM 50	PMT50	50	50	18	\$306.00	20
PTM70	PMT70	70	70	26	\$349.00	25
PTM100	PMT100	100	100	37	\$497.00	30
PTM135	PMT135	135	135	50	\$612.00	40

For replacement cartridges, see page 18.

* Please refer to page 14 for the Sta-Rite Pumps to be used with the Sta-Rite System.

